

TANK-610-BW

无风扇嵌入式系统



Features

- » Intel® Celeron® N3160 处理器
- » 多个 COM 端口: 六个 RS-232 和两个 RS-232/422/485
- » VGA 和 HDMI 双独立显示
- » mSATA 和一个 x 2.5" SATA 存储设备
- » 宽温区

Specifications

Form factor	
SBC Form Factor	CPU:
	Intel® Celeron® N3160 processor (up to 2.24GHz, quad-core, 2MB cache, TDP=6W)
	Chipset:SoC
	System Memory:
	2 x 204-pin DDR3L 1.35V SDRAM SO-DIMM (system Max : 8GB)
I/O Interface	
I/O Ports	4 x USB 3.0
	Ethernet:
	2 x RJ-45 PCIe GbE by Intel® I210-IT
	COM Port:
	6 x RS-232, 2 x RS-232/422/485
	Display:1 x VGA, 1 x HDMI
	Resolution:
	VGA: Up to 2560 x 1600, HDMI: Up to 3840 x 2160
	Audio:1 x Line-out, 1 x Mic-in
	Wireless:1 x 802.11 b/g/n (optional)
Expansion Slots	
Expansion Slots	PCIe Mini:1 x Full size (support mSATA, co-lay SATA), 1 x Half size
System	
Cooling method / System Fan	Fanless
Drive Bays	1 x 2.5' SATA 6Gb/s HDD/SSD Bay
Color	
Color	Black C + Silver
Dimensions	
Dimensions	184 x 200.6 x 58.2
Weight	
Weight	2.2 kg/3 kg
Environment	

Operating Temperature	-40°C ~ 60°C with air flow (SSD)
Humidity	10% ~ 95%, non-condensing

Ordering Information

TANK-610-BW-N3/2G-R10	Fanless wide temperature embedded system with Intel® Celeron® N3160 1.6GHz,(up to 2.24 GHz,quad-core,TDP 6W),2GB DDR3L pre-installed memory,9 V~36 V DC,with RS-232/422/485,USB 3.0,VGA/HDMI,dual Intel® PCIe GbE,RoHS
-----------------------	--

Packing List

1 x 电源线	1 x 电源适配器 (符合 PSE & ErP)
1 x 壁挂式支架	1 x 螺丝组