

iRIS2-2600

IPMI 2.0 adapter card with AST2600 BMC chip for M.2 B Key 3080 socket interface



Features

- » IPMI 2.0 based remote management
- » Out-of-Band management
- » Hardware health monitor
- » Secured remote KVM or virtual media
- » Remote power control

Specifications

尺寸类型	
尺寸类型	M.2 B Key 3080 socket type
物理特性	
尺寸 (LxWxH) (mm)	30mm x 80mm x 7.6mm
净重	18g
I/O 接口	
显示输出	Display Port : Display Port Connector
网络	描述: 10/100/1000Mbps
Other Features	
iRIS	--- IPMI 2.0 Based Management ---
	» BMC stack with a full IPMI 2.0 implementation
	» Customizable sensor management
	» OS Platform Independent
	--- Hardware Health Monitor ---
	» System/CPU temperature
	» Fan speeds
	» Voltage
	» Chassis intrusion
	» Power supply failed
	» FRU (Field Replaceable Unit)
	--- Event Log ---
	» BIOS event
	» Hardware health monitor event
	» Sensor readings
	--- LDAP Support ---
	» Direct LDAP support from the device
	» Open LDAP (Generic LDAP) supported
	--- Media Redirection ---
	» Virtual Media allows users to remotely mount given ISO/IMG drive images through BMC to Server

	» Support for USB key
	» Completely secured (Authenticated or Encrypted) remote KVM or virtual media
	--- Remote Power Control ---
	» Remote power control
	» Keyboard, Video & Mouse (KVM) over IP (iRIS2-2600 only)
	» Serial over LAN (SOL)
	--- User Management ---
	» IPMI based user management
	» Added security with SSL (HTTPS)
	» Multiple user permission level
	» Multiple user profiles
	--- Web-based Configuration ---
	» Full configuration using web UI
	» Fail-safe firmware upgrade
	» Multi-language support in Web interface with English as the currently supported language
环境	
操作温度	-10°C ~ 60°C
Humidity	5% ~ 95%, non-condensing

Ordering Information

iRIS2-2600-R10	IPMI 2.0 adapter card with AST2600 BMC chip for M.2 E Key 3080 socket interface
----------------	---------------------------------------------------------------------------------

Packing List

1 x iRIS2-2600 IPMI 2.0 adapter card	
--------------------------------------	--