

DRPC-242-ADL-P

无风扇 DIN 导轨嵌入式系统



Features

» Supported CPUs:

Intel® Core™ i7-1370PE (up to 4.8GHz, 14-core, 28W TDP)

Intel® Core™ i7-1260P (up to 4.7GHz, 12-core, 28W TDP)

Intel® Core™ i5-1340PE (up to 4.5GHz, 12-core, 28W TDP)

» 2 x USB 3.2 Gen2 & 4 x USB 2.0

» 2 x RS-232 & 2 x RS-422/485 (待2.5KV隔离)

» 符合CE/FCC

Specifications

Form factor	
SBC Form Factor	» Supported CPU:
	Intel® Core™ i7-1370PE (up to 4.8GHz, 14-core, 28W TDP)
	Intel® Core™ i7-1260P (up to 4.7GHz, 12-core, 28W TDP)
	Intel® Core™ i5-1340PE (up to 4.5GHz, 12-core, 28W TDP)
	» 芯片组:
	SoC
	» 系统内存:
	2 x SO-DIMM slot DDR4 3200 MHz (预装8GB) (最大上限64GB)
	» 电源:
	3针凤凰端子: 12-28V直流
	功耗: 12V@4.46A (Intel® Core™ i7-1260P 带8GB DDR4内存)
I/O Interface	
I/O Ports	» USB:
	2 x USB 3.2 Gen2
	4 x USB 2.0
	» 网络:
	1 x 2.5 GbE by Intel® I226LM controller support iAMT
	2 x 2.5 GbE by Intel® I226-V controller
	» 显示:
	1 x lockable HDMI™ 1.4b (up to 4096 x 2160@30Hz)
	1 x DP 1.4b (up to 4096 x 2160 @60Hz)
	» COM Port:
	2 x RS-232 (DB9 with 2.5KV isolation)
	2 x RS-232 (选配)
	2 x RS-422/485 with AFC (DB9 with 2.5KV isolation)
	» GPIO:
	1 x 12-bit(6-in, 6-out)(选配)
	» TPM:

	支持 Intel PTT
	» 看门狗定时器 :
	可编程 1 ~ 255 秒/分钟
Expansion Slots	
Expansion Slots	» M.2:
	1 x 2230 A-key (PCIe Gen3 x1/USB 2.0) Support Vpro
	1 x 3042/52 B-key (PCIe Gen3 x1/USB 3.2 Gen2/USB 2.0)
	1 x 板载SIM 卡槽 (hinge type) for M.2 B key
	1 x 2280 M-key (PCIe Gen4 x4)
	» Backplane:
	1 x PCIe Gen3 x4 (选配)
System	
Cooling method / System Fan	无风扇
	4-pin 外部风扇接口
Drive Bays	1 x 2.5" SATA 6Gb/s SSD bay
Indicator&Buttons	
Buttons	1 x 电源开关
	1 x 2-pin凤凰端子远程开关接口
	1 x 复位开关
	1 x AT/ATX 开关
Indicators	1 x 电源灯
	1 x 硬盘灯
Physical Characteristics	
Construction	铝合金
Color	
Color	黑色
Dimensions	
Dimensions	81 x 150 x190 mm
Weight	
Weight	1.88 / 2.66KG
Environment	
工作温度	-20°C ~ 60°C 带0.7M/S气流 (SSD)
相对湿度	10% ~ 95% 无冷凝
Operating Vibration	10-500 Hz,1.04 Grms, random, 1 hr/axis
Operating Shock	Half-sine wave shock 5G, 11ms, 100 shocks per axis
安规&电磁	CE, FCC, UKCA
OS Compatible	
OS Compatible	Microsoft® Windows® 10/11, Linux

Ordering Information

DRPC-242-ADL-P-Ri7ECS-R11	Embedded system with 13th Gen Intel® Core™ i7-1370PE, TDP 28W, 8GB DDR4 pre-installed memory, HDMI/DP, 3 x 2.5GbE LAN, 4 x COM, 6 x USB, 12~28V DC, RoHS
DRPC-242-ADL-P-Ri5ECS-R11	Embedded system with 13th Gen Intel® Core™ i5-1340PE, TDP 28W, 8GB DDR4 pre-installed memory, HDMI/DP, 3 x 2.5GbE LAN, 4 x COM, 6 x USB, 12~28V DC, RoHS
DRPC-242-ADL-P-Ri3ECS-R11	Embedded system with 13th Gen Intel® Core™ i3-1320PE, TDP 28W, 8GB DDR4 pre-installed memory, HDMI/DP, 3 x 2.5GbE LAN, 4 x COM, 6 x USB, 12~28V DC, RoHS

Packing List

1 x DIN导轨安装支架	1 x 螺丝包
1 x 凤凰端子	