


## PPC-FW19C-Q370

18.5" Intel® Coffee Lake panel PC



## Features

- » 18.5" Panel PC with 8th Generation LGA 1151 Intel® Core™ i7/i5/i3 and Pentium® processor
- » Four hot-swappable and accessible HDD drive bays, support RAID 0/1/5/10
- » Two PCIe 3.0 by 4 and two PCIe 3.0 by 8 slots
- » Dual M.2 2280 PCIe Gen 3.0 x4 NVMe™ SSD support
- » QTS-Gateway support

## Specifications

| Display                  |                                                                  |
|--------------------------|------------------------------------------------------------------|
| Backlight MTBF(hrs)      | 50000                                                            |
| Brightness(cd/m2)        | 400                                                              |
| Contrast Ratio           | 1000:1                                                           |
| LCD Size                 | 18.5"                                                            |
| Max Resolution           | 1366x768                                                         |
| Environment              |                                                                  |
| Humidity                 | 5% ~95%, non-condensing                                          |
| IP Level                 | IP66 compliant front panel                                       |
| Operating Temperature    | -20°C ~ 50°C (with SSD and TDP 65W processor)                    |
|                          | -20°C ~ 40°C (with HDD or add-on cards without fan)              |
| Safety & EMC             | CE, FCC                                                          |
| Storage Temperature      | -30°C ~ 60°C                                                     |
| Expansion Slots          |                                                                  |
| Expansion Slots          | 2 x PCIe 3.0 by 8 (by 16 slot)                                   |
|                          | 2 x PCIe 3.0 by 4 ( maximum card size supported: 68 mm x 167 mm) |
| Form factor              |                                                                  |
| Form factor              | 8th Genertion Intel Core™ i7/i5/i3 porcessors in the LGA 1151    |
|                          | Intel® 300 Series Chipsets Q370                                  |
| I/O Interface            |                                                                  |
| Ethernet                 | Intel® I211AT Ethernet controllers                               |
| Other Features           |                                                                  |
| TPM                      | Support(2x10pin, P=2.54mm)                                       |
| Physical Characteristics |                                                                  |
| Color                    | Front frame: Cyan-blue (PSM 296C); Others: Black C               |
| Cutout Dimensions        | 447.8x267.2                                                      |
| Dimensions (LxWxH) (mm)  | 470x290x121                                                      |
| Mounting                 | Panel/Rack mount                                                 |
| Net Weight               | 8.5                                                              |

| Power                       |                                                                                             |
|-----------------------------|---------------------------------------------------------------------------------------------|
| Power Supply                | AC input ATX power supply                                                                   |
|                             | 1. 250 W power supply                                                                       |
|                             | - Input: 115VAC~230VAC, 50/60Hz                                                             |
|                             | - Output (max.): 3.3V@12A, 5V@14A, 12V@25A, -12V@0.3A,+5Vsb@3A                              |
|                             | 2. 350 W power supply (Build to Order)                                                      |
|                             | - Input: 115VAC~264VAC, 50/60Hz                                                             |
|                             | - Output (max.): 3.3V@14A, 5V@16A, 12V@29A, -12V@0.3A,+5Vsb@3A                              |
|                             | - Efficiency: Full load (100%) 87%, Typical load (50%) 90%, Light load (20%) 87%            |
| Storage                     |                                                                                             |
| Storage                     | 4 x Hot-swappable SATA 6G/s HDD/SSD bay (support RAID 0/1/5/10)                             |
|                             | 2 x M.2 M-key (2280, PCIe 3.0 x4), support NVMe SSD                                         |
| System                      |                                                                                             |
| Chipset                     | Intel® 300 Series Chipsets Q370                                                             |
| Cooling method / System Fan | System fan                                                                                  |
| CPU                         | 8th Generation LGA1151 Intel® Core™ i7/i5/i3 and Pentium® CPU                               |
| Memory Max.                 | Two 288-pin 2666/2400 MHz dual-channel unbuffered DDR4 SDRAM DIMM slots (system max. 64 GB) |
| Touch                       |                                                                                             |
| Touch Controller            | EETI EXC3188                                                                                |
| Touch Screen                | 10-point Projected capacitive touch window, 6H                                              |
|                             | (Anti-UV, Anti-glare Surface)                                                               |
| I/O Interface               |                                                                                             |
| I/O Interface               | 1 x AT/ATX switch                                                                           |
|                             | 1 x HDMI™                                                                                   |
|                             | 2 x LAN                                                                                     |
|                             | 1 x Line out                                                                                |
|                             | 1 x Mic                                                                                     |
|                             | 1 x Power Switch                                                                            |
|                             | 1 x Reset Button                                                                            |
|                             | 2 x RS-232                                                                                  |
|                             | 6 x USB 3.0                                                                                 |

## Ordering Information

|                             |                                                                                                                                                                                            |
|-----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| PPC-FW19C-Q370-i7/PC/25-R10 | 18.5" 400cd/m² 1366 x 768 AI modular Panel PC, Intel® Core™ i7-8700T Processor (6-core,12-thread,2.4 GHz) TDP 35W, two PCIe x4 and two PCIe x8 slots, four HDD bays, 250W PSU, R10         |
| PPC-FW19C-Q370-i5/PC/25-R10 | 18.5" 400cd/m² 1366 x 768 AI modular Panel PC, Intel® Core™ i5-8500T Processor (6-core, 6-thread, 2.1 GHz) TDP 35W, two PCIe x4 and two PCIe x8 slots, four HDD bays, 250W PSU, R10        |
| PPC-FW19C-Q370-i3/PC/25-R10 | 18.5" 400cd/m² 1366 x 768 AI modular Panel PC, Intel® Core™ i3-8100T Processor (4-core, 4-thread, 3.10 GHz) TDP 35W, two PCIe x4 and two PCIe x8 slots, four HDD bays, 250W PSU, R10       |
| PPC-FW19C-Q370-P/PC/25-R10  | 18.5" 400cd/m² 1366 x 768 AI modular Panel PC, Intel® Pentium® Gold G5400T Processor (2-core, 4-thread, 3.10 GHz) TDP 35W, two PCIe x4 and two PCIe x8 slots, four HDD bays, 250W PSU, R10 |

## Packing List

|            |              |
|------------|--------------|
| Power cord | HDD door key |
|------------|--------------|