

PuIM-10G4SF-MLX

Mellanox ConnectX-4 Lx based Network Interface Card support Quad 10GbE with 4 x SFP+ by 2 PCIe 3.0 x 4 Interface



Features

- » 2 x Mellanox ConnectX-4
- » 4 ports 10 GbE SFP+ connector
- » 2 PCIe 3.0 x4
- » RoHS compliant

Specifications

Physical Characteristics	
Dimensions (LxWxH) (mm)	165.50 (L) x 77.8 (W) x 44.2 (H)
I/O Interface	
Ethernet	4 x SFP+
Environment	
Operating Temperature	0°C ~ 40°C (32°F ~ 104°F)
Storage Temperature	-20°C ~ 75°C (-4°F ~ 167°F)
Humidity	5% ~ 90% RH, Non-condensing
Certifications	
Safety & EMC	RoHS/CE/FCC compliant
Card Slot Interface	
PCIe	2 PCIe 3.0 x4
Card Features	
Speed	1GbE/10GbE
Controller Chip	Mellanox ConnectX-4

Ordering Information

PuIM-10G4SF-MLX-R10	Mellanox ConnectX-4 Lx based Network Interface Card support Quad 10GbE with 4 x SFP+ by 2 PCIe 3.0 x 4 Interface.
---------------------	---

Packing List

1 x PuIM-10G4SF-MLX module	1 x L-shaped T10 Plum Wrench
1 x QIG	